

ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of STANDARD SERIE YS9007AJ

Product	Product Category	Coating
PTFE GLASS FABRIC	STANDARD SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1250 mm	39.5, 49.3 inches
Thickness	0.07 mm	0.0028 inches
Coated weight	130 g/m ²	3.85 oz/yd ²
PTFE content	62%	62%
Tensile Stength	174 N/cm Warp	99 lbs/inches Warp
	130 N/cm Fill	74 lbs/inches Fill
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Standard Series has smooth, non porous and good release coating, offering longer release life and improved heat transfer.

Applications of PTFE coated fiberglass include release sheet for heat press machines, light weight belt for food industry and rubber extrusion lines, Non stick baking liner or oven liner, electrical insulation and industrial processing.

0.07mm Teflon coated fiberglass is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
 Jiangsu Eson New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-8759020 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com